

DATASHEET: PTDZA is a double sided acrylic tape 35°C

DESCRIPTION:

The PTDZA is a low cost double sided tape, with a max. Temp of 35°C

TECHNICAL INFO:

VALUE

Construction

Adhesive

Acrylic, Solvent based 0.041mm

Carrier

Polyester

Adhesive

Acrylic, Solvent based 0.041mm

Liner

PE-Coated siliconized paper

Total Thickness

0.095mm

Colour

Clear

Adhesion to Steel

800 cN/cm

Static Hear

6 N/625mm²

Rolling Ball Track

10 cm

Temperature Resistant (Short)

120°C

Service Temperature

-20 to 100 °C

Application Temperature

10 to 35°C

Resistant against UV

Yes

HANGON ADVISE:

A low cost double sided acrylic tape.

Used in the wet paint industry.

Easy to position a lot of small parts to a surface.

TYPICAL APPLICATIONS:

- Splicing Paper, Film
- General mounting, laminating
- Roller Binds
- Very high Tack
- Proper roll Pickup
- No splice failures

AGING AND STORAGE

Shelf life is 12 Months from date of manufacture when stored in its original packaging in a clean, dry environment between 15-25°C and 40-50% relative humidity.

Once removed from its packaging, rolls should be protected against direct sunlight and dust.

Best results are obtained when applied to clean, dry surfaces between 5-40°C