

DATASHEET: TH (F60) Aluminium Glasvezel Tape 260°C

DESCRIPTION:

The TH tape is a masking tape for Plasma flame spraying .
It's perfect for Heat Shielding, harness wraps, wire harnessing for aircraft

TECHNICAL DATA:

VALUE

| | |
|--------------------------------|-----------|
| Total Thickness | 0.178mm |
| Color | White |
| Adhesion to Steel | 747 cN/cm |
| Elongation at Break | 7% |
| Temperature Short | 275°C |
| Temperature Service | 260°C |
| Application temperature | 5-35°C |
| Resistant against UV | Yes |
| Resistant against Plasticizers | Yes |
| Resistant against Chemicals | Yes |

HANGON ADVISE:

A tape used in enviroments where high temperatures are used.
The aluminium shield protects surfaces against high temperatures.

FEATURES:

- Provides excellent reflective and conductive characteristics
- Excellent adhesion at high temperatures
- Will remove cleanly

AGING AND STORAGE

Shelf life is 12 Months from date of manufacture when stored in its original packaging in a clean, dry enviroment between 15-25°C and 40-50% relative humidity.
Once removed from it's packaging, rolls should be protected against direct sunlight and dust.
Best reluts are obtained when applied to clean, dry surfaces between 5-35°C